PLASMA > PLASMA SLINGS

# 2" x 20' Plasma® Eye & Eye Sling

SKU: 2-EE-UHMPE-20 Item weight: 28.5 lbs

| LENGTH | CAPACITY | MATERIAL |
|---|---|---|
| 24" | 71,000 lbs. | HMPE |

## SPECIFICATIONS

| | |
|---|---|
| **SKU** | 2-EE-UHMPE-20 |
| **Safety Factor** | 5:1 |
| **30 Degree Capacity** | 71,000 lbs. |
| **45 Degree Capacity** | 100,400 lbs. |
| **60 Degree Capacity** | 122,900 lbs. |
| **Vertical Capacity** | 71,000 lbs. |
| **Choker Capacity** | 49,700 lbs. |
| **Basket Capacity** | 142,000 lbs. |
| **Diameter** | 2" |
| **Eye Length** | 24" |
| **Length** | 20' |
| **Rope Construction** | 12x12 |
| **Material** | HMPE |
| **Product Weight** | 28.5 lbs. |

### SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.

**Current price & availability: heavyhaulrigging.com/p/2-20-plasma-eye-eye-sling**


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.