

WIRE ROPE > 6X19 GALVANIZED WIRE ROPE

3/4" 6x19 Galvanized Wire Rope - EIPS IWRC | 2,500' Coil - Domestic

SKU: 34GWR626-2500FT-D Item weight: 2,600 lbs

|                         |       |        |
|-------------------------|-------|--------|
| BREAK STRENGTH          | GRADE | LENGTH |
| 29.4 tons / 58,800 lbs. | EIPS  | 2,500' |

SPECIFICATIONS

|                            |                                                                                                                    |
|----------------------------|--------------------------------------------------------------------------------------------------------------------|
| SKU                        | 34GWR626-2500FT-D                                                                                                  |
| Assembly Break Strength    | 29.4 tons / 58,800 lbs.                                                                                            |
| Rated for Overhead Lifting | Yes                                                                                                                |
| Grade                      | EIPS                                                                                                               |
| Wire Rope Diameter         | 3/4"                                                                                                               |
| Length                     | 2,500'                                                                                                             |
| Wire Rope Class            | 6x19                                                                                                               |
| Rope Construction          | 6x26                                                                                                               |
| Core                       | IWRC                                                                                                               |
| Finish                     | Galvanized                                                                                                         |
| Product Weight             | 2600 lbs.                                                                                                          |
| Weight Per Foot            | 1.04 lbs.                                                                                                          |
| Standards                  | Meets all dimensional and strength requirements of Federal Specification RR-W-410 (latest revision) and ASTM A1038 |
| Additional Info            | Right Hand Regular Lay                                                                                             |

**SAFETY INFORMATION**

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

**Current price & availability:** [heavyhaulrigging.com/p/3-4-6x19-galvanized-wire-rope-eips-iwrc-2-500-coil](https://heavyhaulrigging.com/p/3-4-6x19-galvanized-wire-rope-eips-iwrc-2-500-coil)