WIRE ROPE > 6X19 GALVANIZED WIRE ROPE

# 3/4" 6x19 Galvanized Wire Rope - EIPS IWRC | Linear Foot - Domestic

SKU: 34GWR626-D Item weight: 1.04 lbs

| BREAK STRENGTH | GRADE | LENGTH |
|---|---|---|
| 29.4 tons / 58,800 lbs. | EIPS | 1' |

## SPECIFICATIONS

| | |
|---|---|
| **SKU** | 34GWR626-D |
| **Assembly Break Strength** | 29.4 tons / 58,800 lbs. |
| **Rated for Overhead Lifting** | Yes |
| **Grade** | EIPS |
| **Wire Rope Diameter** | 3/4" |
| **Length** | 1' |
| **Wire Rope Class** | 6x19 |
| **Rope Construction** | 6x26 |
| **Core** | IWRC |
| **Finish** | Galvanized |
| **Product Weight** | 1.04 lbs. |
| **Weight Per Foot** | 1.04 lbs. |
| **Standards** | Meets all dimensional and strength requirements of Federal Specification RR-W-410 (latest revision) and ASTM A1034 |
| **Additional Info** | Right Hand Regular Lay |


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.

## SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

**Current price & availability: heavyhaulrigging.com/p/3-4-6x19-galvanized-wire-rope-eips-iwrc-linear-foot**



Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.