

CHAIN SLINGS > SINGLE LEG

3/8" x 16' Single Leg Chain Sling w/ Self-Locking & Self-Locking Hooks - Grade 100

SKU: 38G100SSLSL-16 Item weight: 30.6 lbs

|                    |       |            |        |
|--------------------|-------|------------|--------|
| WORKING LOAD LIMIT | GRADE | CHAIN SIZE | LENGTH |
| 8,800 lbs.         | 100   | 3/8"       | 16'    |

SPECIFICATIONS

|                            |                                                                                    |
|----------------------------|------------------------------------------------------------------------------------|
| SKU                        | 38G100SSLSL-16                                                                     |
| Working Load Limit (lbs.)  | 8,800 lbs.                                                                         |
| Safety Factor              | 4:1                                                                                |
| Rated for Overhead Lifting | Yes                                                                                |
| Grade                      | 100                                                                                |
| Length                     | 16'                                                                                |
| Chain Size                 | 3/8"                                                                               |
| End Fitting                | Self-Locking Hook                                                                  |
| Type                       | SSLSL                                                                              |
| Product Weight             | 30.6 lbs.                                                                          |
| Standards                  | Meets or exceeds all ASTM A906 / A906M & ASME B30.10 requirements. AWRF Accredited |
| Manufacturer Name          | KWB                                                                                |
| Additional Info            | Made to order.                                                                     |

**SAFETY INFORMATION**

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

**Current price & availability:** [heavyhaulrigging.com/p/3-8-x-16-single-leg-chain-sling-w-self-locking-self-locking-hooks-gra...](https://heavyhaulrigging.com/p/3-8-x-16-single-leg-chain-sling-w-self-locking-self-locking-hooks-gra...)