WIRE ROPE SLINGS > TYPE 315 THREE PART BRAID SLINGS

3/4" x 20' Three Part Braided Wire Rope Sling

SKU: 3PBS-34-20 Item weight: 70 lbs

LENGTH	CAPACITY
20"	14 ton

SPECIFICATIONS

SKU	3PBS-34-20
Safety Factor	5:1
Vertical Capacity	14 ton
Choker Capacity	10.5 ton
Basket Capacity	28 ton
Diameter	3/4"
Eye Length	20"
Length	20'
Body Diameter	1-1/2"
Wire Rope Class	6x36WS
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/3-4-x-20-three-part-braided-wire-rope-sling

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 1, 2026.