WIRE ROPE SLINGS > TYPE 315 THREE PART BRAID SLINGS

7/8" x 12' Three Part Braided Wire Rope Sling

SKU: 3PBS-78-12 Item weight: 80 lbs

LENGTH	CAPACITY
22"	19 ton

SPECIFICATIONS

SKU	3PBS-78-12
Safety Factor	5:1
Vertical Capacity	19 ton
Choker Capacity	14.3 ton
Basket Capacity	38 ton
Diameter	7/8"
Eye Length	22"
Length	12'
Body Diameter	1-3/4"
Wire Rope Class	6x36WS
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/7-8-x-12-three-part-braided-wire-rope-sling

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 1, 2026.