

BLOCKS & PULLEYS > 4040 TAILBOARD BLOCK

4040 Tailboard Block (3/8" wire x 3" sheave)

SKU: 4040T3 Item weight: 2 lbs

WORKING LOAD LIMIT	BREAK STRENGTH
4,000 lbs.	16,000 lbs.

SPECIFICATIONS

SKU	4040T3
Working Load Limit (lbs.)	4,000 lbs.
Assembly Break Strength	16,000 lbs.
Safety Factor	5:1
Wire Rope Diameter	3/8"
Sheave Diameter	3"
Type	Bronze Bushing
Product Weight	2 lbs.
Standards	Meets or exceeds All ASME B30.26 requirements.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/4040-tailboard-block-3-8-wire-x-3-sheave