WIRE ROPE > 6X19 GALVANIZED WIRE ROPE

5/8" 6x19 Galvanized Wire Rope - EIPS IWRC | 250' Coil - Domestic

SKU: 58GWR626-250FT-D Item weight: 180 lbs

BREAK STRENGTH	GRADE	LENGTH
20.6 tons / 41,200 lbs.	EIPS	250'

SPECIFICATIONS

SKU	58GWR626-250FT-D
Assembly Break Strength	20.6 tons / 41,200 lbs.
Rated for Overhead Lifting	Yes
Grade	EIPS
Wire Rope Diameter	5/8"
Length	250'
Wire Rope Class	6x19
Rope Construction	6x26
Core	IWRC
Finish	Galvanized
Product Weight	180 lbs.
Weight Per Foot	0.72 lbs.
Standards	Meets all dimensional and strength requirements of Federal Specification RR-W-410 (latest revision) and ASTM A1029
Additional Info	Right Hand Regular Lay

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/5-8-6x19-galvanized-wire-rope-eips-iwrc-250-coil-1

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.