WIRE ROPE > 7X19 GALVANIZED WIRE ROPE

3/16" 7x19 Galvanized Aircraft Cable - IPS | Linear Foot

SKU: 719GAC316 Item weight: 0.06 lbs

BREAK STRENGTH	GRADE	LENGTH
2.1 tons / 4,200 lbs.	IPS	1'

SPECIFICATIONS

SKU	719GAC316
Assembly Break Strength	2.1 tons / 4,200 lbs.
Rated for Overhead Lifting	Yes
Grade	IPS
Wire Rope Diameter	3/16"
Length	1'
Wire Rope Class	7x19
Finish	Galvanized
Product Weight	0.07 lbs.
Weight Per Foot	0.07
Standards	Meets all dimensional and strength requirements of Federal Specification RR-W-410 (latest revision) and ASTM A1023
Additional Info	Right Hand Regular Lay Not intended for Aircraft Use

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 12, 2026.

Current price & availability: heavyhaulrigging.com/p/3-16-7x19-galvanized-wire-by-linear-foot

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 12, 2026.