WIRE ROPE > 7X19 VINYL COATED GALVANIZED WIRE ROPE

5/16" 7x19 Vinyl-Coated Aircraft Cable - Galvanized IPS | Linear Foot

SKU: 719VCGAC51638 Item weight: 0.2 lbs

BREAK STRENGTH	GRADE	LENGTH
4.9 tons / 9,800 lbs.	IPS	1'

SPECIFICATIONS

SKU	719VCGAC51638
Assembly Break Strength	4.9 tons / 9,800 lbs.
Rated for Overhead Lifting	Yes
Grade	IPS
Wire Rope Diameter	5/16" Wire Rope / 3/8" With Coating
Length	1'
Wire Rope Class	7x19
Finish	Clear Vinyl (PVC) / Galvanized
Product Weight	0.2 lbs.
Weight Per Foot	0.2
Standards	Meets all dimensional and strength requirements of Federal Specification RR-W-410 (latest revision) and ASTM A1023
Additional Info	Right Hand Regular Lay Not intended for Aircraft Use

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.

Current price & availability: heavyhaulrigging.com/p/5-16-7x19-vinyl-coated-galvanized-wire-by-linear-foot

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.