WIRE ROPE > 7X19 VINYL COATED STAINLESS WIRE ROPE

# 1/8" 7x19 Vinyl-Coated Aircraft Cable - Type 304 Stainless Steel | 250 ft.

SKU: 719VCSSAC18316-250FT Item weight: 9 lbs

| BREAK STRENGTH | GRADE | LENGTH |
|---|---|---|
| 0.88 tons / 1,760 lbs. | 304 Stainless Steel | 250' |

## SPECIFICATIONS

| | |
|---|---|
| **SKU** | 719VCSSAC18316-250FT |
| **Assembly Break Strength** | 0.88 tons / 1,760 lbs. |
| **Rated for Overhead Lifting** | Yes |
| **Grade** | 304 Stainless Steel |
| **Wire Rope Diameter** | 1/8" Wire Rope / 3/16" With Coating |
| **Length** | 250' |
| **Wire Rope Class** | 7x19 |
| **Finish** | Clear Vinyl (PVC) |
| **Product Weight** | 9 lbs. |
| **Weight Per Foot** | 0.04 lbs. |
| **Standards** | Meets all dimensional and strength requirements of Federal Specification RR-W-410 (latest revision) and ASTM A1023 |
| **Additional Info** | Right Hand Regular Lay Not intended for Aircraft Use |

### SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.

**Current price & availability: heavyhaulrigging.com/p/1-8-7x19-vinyl-coated-aircraft-cable-type-304-250-ft**


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.