BOLTHOLD ASPHALT ANCHORS

Bolthold AM625 Asphalt Anchor, Molded Plastic, 6 Pkg

SKU: AM625 Item weight: 1 lbs

LENGTH

3"-6"

SPECIFICATIONS

SKU	AM625
Diameter	3/4"
Length	3"-6"
Head Diameter	1.2"
Thread Type	1/4" Internal Thread
Head Type	T30 Torx Head
Torque	200 lb.-in.
Manufacturer Name	Bolthold Asphalt anchors
Quantity	6
Additional Info	Shear Resistance: 1000 lbs. Pull Force: 1500 lbs.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/bolthold-am625-asphatl-anchor-molded-plastic-6-pkg

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 14, 2026.