L-TRACK

# 72" Aluminum L-Track | Anodized Finish

SKU: AT72AL-AN Item weight: 4 lbs

| WIDTH | LENGTH | MATERIAL |
|---|---|---|
| 1-1/8" | 6' | 6061T-T6 Aluminum |

## SPECIFICATIONS

| | |
|---|---|
| **SKU** | AT72AL-AN |
| **Width** | 1-1/8" |
| **Length** | 6' |
| **Height** | 0.5" |
| **Material** | 6061T-T6 Aluminum |
| **Finish** | Anodized |
| **Color** | Unpainted |
| **Style** | Track Only |
| **Type** | Standard L-Track |
| **Product Weight** | 2.24 lbs. |
| **Quantity** | Single |
| **Additional Info** | Mount Type: Flush & Surface Mount Drilled Hole Diameter: 1/4" Compatible Fasteners: 1/4", 6mm, or #12 fasteners Drilled Holes: 15 Connection Points: 72 |

### SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.

**Current price & availability: heavyhaulrigging.com/p/72-anodized-l-track**



Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.