LIFTING BEAMS AND SPREADER BARS > CONTAINER LIFTING BEAMS

# Container Lifting Beam - 4,000 Lb. Capacity - 3' Max Spread

SKU: BCLB4K36 Item weight: 135 lbs

**WORKING LOAD LIMIT**
**4,000 lbs.**

**MATERIAL**
**Steel**

## SPECIFICATIONS

| | |
|---|---|
| **SKU** | BCLB4K36 |
| **Working Load Limit (lbs.)** | 4,000 lbs. |
| **Safety Factor** | 3:1 |
| **Rated for Overhead Lifting** | Yes |
| **Spread** | 3' |
| **Bail Dimensions** | Inside Width: 4" Inside Length: 5" Top Thickness: 1" |
| **Material** | Steel |
| **Finish** | High visibility yellow powder coated paint |
| **Product Weight** | 120 lbs. |
| **Standards** | Exceeds all ASME B30.20 and OSHA regulations. Proof loaded per OSHA requirements. |
| **Manufacturer Name** | M&W |
| **Brand Part Number** | 13325 |
| **Additional Info** | WLL (tons): 2 Headroom: 10" |


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 12, 2026.

## SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

**Current price & availability: heavyhaulrigging.com/p/container-lifting-beam-4-000-lb-capacity-3-max-spread**



Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 12, 2026.