

LIFTING BEAMS AND SPREADER BARS > BASKET LIFTING BEAMS

Basket Lifting Beam - 1,000 lb Capacity - 6' Max Spread

SKU: BLB1K6 Item weight: 95 lbs

|                    |          |
|--------------------|----------|
| WORKING LOAD LIMIT | MATERIAL |
| 1,000 lbs.         | Steel    |

SPECIFICATIONS

|                            |                                                                                   |
|----------------------------|-----------------------------------------------------------------------------------|
| SKU                        | BLB1K6                                                                            |
| Working Load Limit (lbs.)  | 1,000 lbs.                                                                        |
| Safety Factor              | 3:1                                                                               |
| Rated for Overhead Lifting | Yes                                                                               |
| Spread                     | 6'                                                                                |
| Bail Dimensions            | Inside Width: 3" Inside Length: 5" Top Thickness: 0.88"                           |
| Material                   | Steel                                                                             |
| Finish                     | High visibility yellow powder coated paint                                        |
| Product Weight             | 80 lbs.                                                                           |
| Standards                  | Exceeds all ASME B30.20 and OSHA regulations. Proof loaded per OSHA requirements. |
| Manufacturer Name          | M&W                                                                               |
| Brand Part Number          | 17493                                                                             |
| Additional Info            | WLL (tons): 0.5 Headroom: 9.5" Hooks designed for 2" eye width                    |

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: [heavyhaulrigging.com/p/basket-lifting-beam-1-000-lb-capacity-6-max-spread](https://heavyhaulrigging.com/p/basket-lifting-beam-1-000-lb-capacity-6-max-spread)