

LIFTING BEAMS AND SPREADER BARS > DURA-LITE 416 ADJUSTABLE BEAM

Caldwell 1/2 Ton x 3 - 4' Adjustable Lifting Beam | Dura-Lite 416-1/2-4

SKU: CASLB1000-4 Item weight: 16 lbs

WORKING LOAD LIMIT

1,102 lbs.

MATERIAL

Fiber-Reinforced Polymer Composite

SPECIFICATIONS

SKU	CASLB1000-4
Working Load Limit (lbs.)	1,102 lbs.
Safety Factor	3:1
Rated for Overhead Lifting	Yes
Throat Opening	0.89"
Spread	3' - 4'
Bail Dimensions	Inside Width: 1.5" Inside Length: 1.9" Diameter: 0.38"
End Fitting	Bottom Swivel Latch Hooks & Top Link Included
Material	Fiber-Reinforced Polymer Composite
Finish	Acrylic Polyurethane
Product Weight	16 lbs.
Standards	Complies with ASME B30.9, BTH-1, and B30.20, design category B, service class 4 regulations.
Manufacturer Name	Caldwell
Brand Part Number	416-1/2-4
Additional Info	WLL (tons): 0.5 Headroom: 14.9" Bail Adjustment Length: 6" Bail Adjustment Increments: 3"

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/dura-lite-composite-adjustable-spreader-lifting-beam-1-000-lb-capaci...