MOVING SUPPLIES > PACKAGING SUPPLIES

3/4" Cordstrap Buckles for Composite Strapping - Pallet

SKU: CB6S-CS-PLT Item weight: 2,443.2 lbs

BREAK STRENGTH	GRADE	MATERIAL
2204 lbf	DNV Witnessed	Galvanized Steel Wire

SPECIFICATIONS

SKU	CB6S-CS-PLT
Assembly Break Strength	2204 lbf
Grade	DNV Witnessed
Size	3/4"
Material	Galvanized Steel Wire
Finish	Galvanized
Type	Galvanized Buckles for Composite Cord Strapping
Operating Temperature	Use between 23°F and 104°F. Store in cool and dry environment.
Product Weight	2443.2 lbs.
Brand	Cordstrap
Brand Part Number	7374500
Quantity	96-Pack (Pallet)
Additional Info	System Breaking Strength: 2204 lbf Linear Breaking Strength: 1377 lbf Elongation at break: 12% Recommended Tensioners: CT20 & CTT20; CT25

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 15, 2026.

Current price & availability: heavyhaulrigging.com/p/3-4-cordstrap-buckles-for-composite-strapping-pallet

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 15, 2026.