



MOVING SUPPLIES > PACKAGING SUPPLIES

1" Cordstrap Buckles for Composite Strapping - Box of 250

SKU: CB8-CS Item weight: 30.56 lbs

BREAK STRENGTH	GRADE	MATERIAL
3306 lbf	DNV Witnessed	Galvanized Steel Wire

SPECIFICATIONS

SKU	CB8-CS
Assembly Break Strength	3306 lbf
Grade	DNV Witnessed
Size	1"
Material	Galvanized Steel Wire
Finish	Galvanized
Type	Galvanized Buckles for Composite Cord Strapping
Operating Temperature	Use between 23°F and 104°F. Store in cool and dry environment.
Product Weight	30.56 lbs.
Brand	Cordstrap
Brand Part Number	7360500
Quantity	Single
Additional Info	System Breaking Strength: 3306 lbf Linear Breaking Strength: 2039 lbf Elongation at break: 12% Recommended Tensioners: CT40/2 & CTT40; CBT35

**SAFETY INFORMATION**

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/1-cordstrap-buckles-for-composite-strapping-box-of-250