CHAINS & BINDERS > SPEEDBINDERS

# 5/16" - 3/8" Crosby® Speedbinder™ Load Binder | TD-66

SKU: CBTD-66-CR Item weight: 14.3 lbs

| WORKING LOAD LIMIT | GRADE | CHAIN SIZE | LENGTH |
|---|---|---|---|
| 6,600 lbs. | 70 / 80 / 100 | 5/16"- 3/8" | 23.02" |

## SPECIFICATIONS

| | |
|---|---|
| **SKU** | CBTD-66-CR |
| **Working Load Limit (lbs.)** | 6,600 lbs. |
| **Safety Factor** | 3:1 |
| **Grade** | 70 / 80 / 100 |
| **Length Closed** | 23.02" |
| **Length Open** | 32.02" |
| **Chain Size** | 5/16"- 3/8" |
| **End Fitting** | Clevis Grab Hook |
| **Ratchet Handle** | Torque Drive |
| **Finish** | Painted |
| **Color** | Black with blue marking |
| **Type** | Torque Drive |
| **Product Weight** | 14.3 lbs. |
| **Standards** | FMCSA / DOT compliant and meet or exceed WSTDA T-6 Recommended Standards |
| **Manufacturer Name** | Crosby® |
| **Brand Part Number** | TD-66 / 3674481 |
| **Additional Info** | Handle length: 15.86" Take up: 9" Hook Throat Opening: .51" |


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.

## SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

**Current price & availability: heavyhaulrigging.com/p/5-16-3-8-crosby-speedbinder-load-binder-td-66**


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.