MOVING SUPPLIES > PACKAGING SUPPLIES

Cordstrap 1-1/4" x 951' Composite Corded Strapping - 2-Pack

SKU: CC105UF-CS-2PK Item weight: 49.8 lbs

BREAK STRENGTH	GRADE	LENGTH	MATERIAL
4960 lbf	AAR Grade 4 &...	951' per roll	High tenacity p...

SPECIFICATIONS

SKU	CC105UF-CS-2PK
Assembly Break Strength	4960 lbf
Grade	AAR Grade 4 & DNV Witnessed
Size	1-1/4"
Length	951' per roll
Core	8" Diameter
Material	High tenacity polyester filament yarn and homopolymer polypropylene
Color	White
Type	Composite Cord Strapping
Operating Temperature	Use between 23°F and 104°F. Store in cool and dry environment.
Product Weight	24.9 lbs.
Brand	Cordstrap
Brand Part Number	7315000
Quantity	2-Pack
Additional Info	System Breaking Strength: 4960 lbf Linear Breaking Strength: 3580 lbf Elongation at break: 12% Recommended Tensioners: CT40/2 & CTT40; CBT35MK2 & CT35PN

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 14, 2026.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/cordstrap-1-1-4-x-951-composite-corded-strapping-2-pack

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 14, 2026.