MOVING SUPPLIES > PACKAGING SUPPLIES

Cordstrap 3/4" x 1969' Composite Corded Strapping

SKU: CC65UF-CS Item weight: 23.22 lbs

BREAK STRENGTH	GRADE	LENGTH	MATERIAL
2204 lbf	DNV Witnessed	1969'	High tenacity p...

SPECIFICATIONS

SKU	CC65UF-CS
Assembly Break Strength	2204 lbf
Grade	DNV Witnessed
Size	3/4"
Length	1969'
Core	8" Diameter
Material	High tenacity polyester filament yarn and homopolymer polypropylene
Color	White
Type	Composite Cord Strapping
Operating Temperature	Use between 23°F and 104°F. Store in cool and dry environment.
Product Weight	23.22 lbs.
Brand	Cordstrap
Brand Part Number	7297000
Quantity	Single
Additional Info	System Breaking Strength: 2204 lbf Linear Breaking Strength: 1377 lbf Elongation at break: 12% Recommended Tensioners: CT20 & CTT20; CT25

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/cordstrap-3-4-x-1969-composite-corded-strapping

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.