

WIRE ROPE SLINGS > CABLE LAID

5/8" x 16' Standard Eye Cable Laid Wire Rope Sling | 7x7x7

SKU: CL1-58-16 Item weight: 11.52 lbs

GRADE	LENGTH	CAPACITY	MATERIAL
EIPS	16'	2.8 tons / 5,600...	Steel

SPECIFICATIONS

SKU	CL1-58-16
Safety Factor	5:1
Vertical Capacity	2.8 tons / 5,600 lbs.
Choker Capacity	2.1 tons / 4,200 lbs.
Basket Capacity	5.6 tons / 11,200 lbs.
Grade	EIPS
Diameter	5/8"
Length	16'
Rope Construction	7x7
Core	IWRC
End Fitting	Turn-Back Eye
Material	Steel
Finish	Galvanized
Product Weight	11.52 lbs.
Standards	Meets or exceeds all ASME B30.9 & OSHA 1910.184 requirements.
Additional Info	Rated capacities for basket hitch based on a D/d ratio of 10/1

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/wire-rope-sling-cable-laid-7x7x7-5-8-x-16