LIFTING BEAMS AND SPREADER BARS > DURA-LITE 430 SPREADER BEAM

# Caldwell 2 Tons x 2' Spreader Beam | Dura-Lite 430-2-2

SKU: CSB4000-2 Item weight: 22 lbs

**WORKING LOAD LIMIT**
**4,409 lbs.**

**MATERIAL**
**Fiber-Reinforced Polymer Composite**

## SPECIFICATIONS

| | |
|---|---|
| **SKU** | CSB4000-2 |
| **Working Load Limit (lbs.)** | 4,409 lbs. |
| **Safety Factor** | 3:1 |
| **Rated for Overhead Lifting** | Yes |
| **Throat Opening** | 0.91" |
| **Spread** | 2' |
| **Bail Dimensions** | Inside Width: 2.8" Inside Length: 5" Diameter: 0.62" |
| **End Fitting** | Bottom Swivel Latch Hooks & Top Rigging Included |
| **Material** | Fiber-Reinforced Polymer Composite |
| **Finish** | Acrylic Polyurethane |
| **Product Weight** | 22 lbs. |
| **Standards** | Complies with ASME B30.9, BTH-1, and B30.20, design category B, service class 4 regulations. |
| **Manufacturer Name** | Caldwell |
| **Brand Part Number** | 430-2-2 |
| **Additional Info** | WLL (tons): 2 Headroom: 27" |


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 12, 2026.

## SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

**Current price & availability: heavyhaulrigging.com/p/dura-lite-composite-spreader-beam-4-000-lb-capacity-2-spread**



Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 12, 2026.