

LIFTING BEAMS AND SPREADER BARS > DURA-LITE 430 SPREADER BEAM

Caldwell 3 Tons x 6' Spreader Beam | Dura-Lite 430-3-6

SKU: CSB6000-6 Item weight: 64 lbs

WORKING LOAD LIMIT	MATERIAL
6,613 lbs.	Fiber-Reinforced Polymer Composite

SPECIFICATIONS

SKU	CSB6000-6
Working Load Limit (lbs.)	6,613 lbs.
Safety Factor	3:1
Rated for Overhead Lifting	Yes
Throat Opening	1"
Spread	6'
Bail Dimensions	Inside Width: 2.8" Inside Length: 5" Diameter: 0.62"
End Fitting	Bottom Swivel Latch Hooks & Top Rigging Included
Material	Fiber-Reinforced Polymer Composite
Finish	Acrylic Polyurethane
Product Weight	64 lbs.
Standards	Complies with ASME B30.9, BTH-1, and B30.20, design category B, service class 4 regulations.
Manufacturer Name	Caldwell
Brand Part Number	430-3-6
Additional Info	WLL (tons): 3 Headroom: 54"

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/dura-lite-composite-spreader-beam-6-000-lb-capacity-6-spread