MOVING SUPPLIES > PACKAGING SUPPLIES

Cordstrap 3/4" x 2034' Woven Cord Strapping - 2-Pack

SKU: CW65-CS-2PK Item weight: 46.9 lbs

BREAK STRENGTH	GRADE	LENGTH	MATERIAL
3485 lbf	DNV Witnessed	2034' per roll	Coated high te...

SPECIFICATIONS

SKU	CW65-CS-2PK
Assembly Break Strength	3485 lbf
Grade	DNV Witnessed
Size	3/4"
Length	2034' per roll
Core	2.99" Diameter
Material	Coated high tenacity polyester filament yarn
Color	White
Type	Woven Cord Strapping
Operating Temperature	Use between 23°F and 104°F. Store in cool and dry environment.
Product Weight	22.5 lbs.
Brand	Cordstrap
Brand Part Number	6928000
Quantity	2-Pack
Additional Info	System Breaking Strength: 2866 lbf Linear Breaking Strength: 2205 lbf Elongation at break: 9-17% Recommended Tensioners: CT25 & CTT25

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 14, 2026.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/cordstrap-3-4-x-1575-woven-cord-strapping-2-pack

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 14, 2026.