

BLOCKS & PULLEYS > DOUBLE SWIVEL BLOCK WITH HOOK

Double Swivel Block w/ Hook & Brass Bushing - 304 Stainless Steel 5/8" x 3"

SKU: DSWIVELB58-3H Item weight: 3.8 lbs

WORKING LOAD LIMIT

1,450 lbs.

BREAK STRENGTH

5,800 lbs.

SPECIFICATIONS

SKU	DSWIVELB58-3H
Working Load Limit (lbs.)	1,450 lbs.
Assembly Break Strength	5,800 lbs.
Safety Factor	4:1
Wire Rope Diameter	5/8"
Sheave Diameter	3"
Type	Brass Bushing
Product Weight	3.8 lbs.
Standards	Meets or exceeds All ASME B30.26 requirements.
Brand Part Number	210S-75-A2

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/double-swivel-block-w-hook-brass-bushing-t304-ss-5-8-x-3