CONNECTING LINKS > CROSBY G-402 EYE & EYE SWIVEL

Crosby® 7/8" Regular Swivel - G-402

SKU: EESWIVEL78-CR Item weight: 6.25 lbs

WORKING LOAD LIMIT	BREAK STRENGTH
10,000 lbs.	**50,000 lbs.**

SPECIFICATIONS

SKU	EESWIVEL78-CR
Working Load Limit (lbs.)	10,000 lbs.
Assembly Break Strength	50,000 lbs.
Safety Factor	5:1
Diameter	7/8"
Finish	Hot Dip Galvanized
Product Weight	6.25 lbs.
Standards	Meets or exceeds ASTM A957 & ASME B30.26 requirements.
Manufacturer Name	Crosby®
Brand Part Number	1016135

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/crosby-7-8-regular-swivel-g-402

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.