

FALL PROTECTION > HARNESSES & BODY WEAR

FallTech Contractor+ Full-Body Climbing Harness | Non-Belted | M | 7016BFDM

SKU: FPBW-7016BFDM Item weight: 4 lbs

MATERIAL

D-ring: Plated alloy steel; 5,000 lb min. static strength Webbing: Polyester; 5,000...

SPECIFICATIONS

SKU	FPBW-7016BFDM
Size	M
Material	D-ring: Plated alloy steel; 5,000 lb min. static strength Webbing: Polyester; 5,000 lb min. static strength Buckles / Adjusters: Plated alloy steel; 3,372 lb min. static strength
Color	Blue and Black
Style	Non-Belted
Type	Fall Arrest and Climbing, 2D
Product Weight	4 lbs.
Standards	ANSI Standards: ANSI Z359.11-2014, OSHA Standards: OSHA 1926.502 and 1910.140, CSA Standards: CSA Z259.10-2018
Manufacturer Name	FallTech
Brand	Contractor Plus
Brand Part Number	7016BFDM

Additional Info OSHA User Capacity: 130 to 425 lb max. ANSI User Capacity: 130 to 310 lb max. Static Strength: 3,600 lb min.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/falltech-contractor-full-body-climbing-harness-non-belted-m-7016bfd...