FALL PROTECTION > HARNESSES & BODY WEAR

FallTech Tradesman Pro Full-Body Construction Harness | Belted | S/M | 7078CSM

SKU: FPBW-7078CSM Item weight: 6.3 lbs

MATERIAL

D-ring: Plated alloy steel; 5,000 lb min. static strength Webbing: Polyester; 5,000...

SPECIFICATIONS

SKU	FPBW-7078CSM
Size	S/M
Material	D-ring: Plated alloy steel; 5,000 lb min. static strength Webbing: Polyester; 5,000 lb min. static strength Buckles / Adjusters: Plated alloy steel; 3,372 lb min. static strength
Color	Red and Black
Style	Belted
Type	Fall Arrest and Work Positioning, 3D
Product Weight	6.25 lbs.
Standards	ANSI Standards: ANSI Z359.11-2021, OSHA Standards: OSHA 1926.502 and 1910.66, CSA Standards: CSA Z259.10-2018
Manufacturer Name	FallTech
Brand	Tradesman® Pro
Brand Part Number	7078CSM
Additional Info	OSHA User Capacity: 130 to 425 lb max. ANSI User Capacity: 130 to 310 lb max. Static Strength: 3,600 lb min.

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 16, 2026.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/falltech-tradesman-pro-full-body-construction-harness-belted-s-m-7...

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 16, 2026.