

FALL PROTECTION > HORIZONTAL SYSTEMS

FallTech 60' Temporary Horizontal Lifeline System w/ Energy Absorber | 2-Person | 77602K

SKU: FPHS-77602K Item weight: 22 lbs

LENGTH	MATERIAL
60'	Rope Material: 11/16" braided 32-str...

SPECIFICATIONS

SKU	FPHS-77602K
Length	60'
Material	Rope Material: 11/16" braided 32-strand solid-core nylon kernmantle; 5,000 lb min. Carabiner Material: Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength Sling Anchor Material: Polyester webbing with plated alloy steel D-rings; 5,000 lb min. static strength Tensioner & Connecting Ring Material: Plated alloy steel; 5,000 lb min. static strength Energy Absorber Material: Polyester tear-away
Product Weight	18 lbs.
Standards	OSHA 1926.502 and 1910.66
Manufacturer Name	FallTech
Brand	FallTech
Brand Part Number	77602K
Additional Info	OSHA User Capacity: 310 lb max. per user; 2 users max. Static Strength: 5,000 lb. min.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/falltech-60-temporary-horizontal-lifeline-system-w-energy-absorber-...