FALL PROTECTION > FALL PROTECTION KITS

FallTech Roofing Fall Protection Kit with Harness | 8595A

SKU: FPK-8595A Item weight: 17.7 lbs

SPECIFICATIONS

SKU	FPK-8595A
Size	S/M/L
Product Weight	17.7 lbs.
Standards	Harness: Complies with ANSI Z359.11-2014 | Anchor: OSHA 1926.502 | Lifeline: ANSI Z359.15-2014 | Lanyard: OSHA 1926.502 and 1910.66
Brand	FallTech
Brand Part Number	8595A
Additional Info	Harness / Anchor / Lifeline ANSI User Capacity: 130 to 310 lb. max Harness / Anchor OSHA User Capacity: 130 to 425 lb. max Lifeline / Lanyard OSHA User Capacity: 130 to 310 lb. max Harness Static Strength: 3,600 lb. min Anchor Static Strength: 5,000 lb. min Lifeline Static Strength: 5,000 lb. min Lanyard Static Strength: 5,000 lb. min Lanyard Max. Arrest Distance: 48" Lanyard: Avg. Arrest Force: 900 lb. Lanyard Max. Arrest Force: 1,800 lb. Lanyard Length: 3'

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/falltech-roofing-fall-protection-kit-with-harness-8595a

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 4, 2026.