FALL PROTECTION > RESCUE AND DESCENT

FallTech 150' Fall Protection Rescue Equipment Kit with Bag | 6814150K

SKU: FPRD-6814150K Item weight: 18 lbs

LENGTH
150'

MATERIAL
Connector: Aluminum alloy; 5,000 lb...

SPECIFICATIONS

SKU	FPRD-6814150K
Length	150'
Material	Connector: Aluminum alloy; 5,000 lb min. static strength with 3,600 lb gate strength Rope: 7/16" kernmantle polyamide blend Housing: Powder coated aluminum
Product Weight	18 lbs.
Standards	ANSI Z359.4-2013
Manufacturer Name	FallTech
Brand	FallTech
Brand Part Number	6814150K
Additional Info	Max Descent Height: 524' for 2 users Max Descent Load: 440 lbs. for 2 users Max Work Lifting Load: 308 lbs. Max Lifting Height: 524' at 440 lbs. Descent Speed: 2.6' per second for 1 user Cumulative Descent Distance: 25,200' or 48 descents with 220 lbs. / 2,620' or 5 descents with 440 lbs.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 14, 2026.

Current price & availability: heavyhaulrigging.com/p/falltech-150-fall-protection-rescue-equipment-kit-with-bag-6814150k

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 14, 2026.