FALL PROTECTION > SELF RETRACTING LIFELINES & PERSONAL FALL LIMITERS

FallTech FT-X LE 8' Cable Self-Retracting Lifeline | Twin-Leg | Snap Hooks | 82808TP1

SKU: FPSRL-82808TP1 Item weight: 8.2 lbs

LENGTH	CAPACITY	MATERIAL
8'	Rated for workers wei...	Cable Material: 3/16"...

SPECIFICATIONS

SKU	FPSRL-82808TP1
Load Capacity	Rated for workers weighing up to 420 pounds, including clothes, tools, gear, etc.
Length	8'
End Fitting	Steel Snap Hook
Material	Cable Material: 3/16" galvanized steel; 3,600 lb min. static strength Anchorage Connector Material: Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength Dorsal Connector Material: Aluminum alloy; 3,600 lb min. Energy Absorber Material: Polyester tear-away
Style	Twin-leg
Type	ANSI Class 2 SRL-P Compliant
Product Weight	8.2 lbs.
Standards	ANSI Z359.14-2021, OSHA 1926.502 and 1910.66, CSA
Manufacturer Name	FallTech
Brand	FT-X™ Cable Leading Edge
Brand Part Number	82808TP1
Additional Info	ANSI User Capacity: 130 to 310 lbs. max. OSHA User Capacity: 130 to 420 lbs. max. Static Strength: 3,600 lbs. min. Avg Arrest Force: 1,350 lbs. max. Max Arrest Distance: 42" Max Arrest Force: 1,800 lbs.

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/falltech-ft-x-le-8-cable-self-retracting-lifeline-twin-leg-snap-hooks-82...

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 2, 2026.