

LIFTING CLAMPS > TERRIER FSVS BEAM LIFTING CLAMPS

Terrier FSVS 2 Ton Screw Beam Lifting Clamp - 962000

SKU: FSVS-2T Item weight: 12.5 lbs

WORKING LOAD LIMIT

4,000 lbs.

SPECIFICATIONS

|                           |                                                                                                                           |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------|
| SKU                       | FSVS-2T                                                                                                                   |
| Working Load Limit (lbs.) | 4,000 lbs.                                                                                                                |
| Eye Diameter              | 2.87"                                                                                                                     |
| Jaw Opening               | 2.95"-16.54"                                                                                                              |
| Type                      | H-Beams                                                                                                                   |
| Product Weight            | 12.5 lbs.                                                                                                                 |
| Manufacturer Name         | Terrier                                                                                                                   |
| Brand Part Number         | 962000                                                                                                                    |
| Additional Info           | All Terrier lifting clamps are tested up to 2x the WLL and are designed with a break factors of 5x the WLL. WLL (tons): 2 |

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: [heavyhaulrigging.com/p/terrier-fsvs-2-ton-screw-beam-lifting-clamp-962000](https://heavyhaulrigging.com/p/terrier-fsvs-2-ton-screw-beam-lifting-clamp-962000)