

TURNBUCKLES > GALVANIZED HOOK & HOOK

5/16" x 4-1/2" Hook & Hook Galvanized Turnbuckle

SKU: HHTBGV516X412 Item weight: 0.5 lbs

WORKING LOAD LIMIT	LENGTH
700 lbs.	9.31"

SPECIFICATIONS

SKU	HHTBGV516X412
Working Load Limit (lbs.)	700 lbs.
Safety Factor	5:1
Rated for Overhead Lifting	No
Diameter	5/16"
Length Closed	9.31"
Length Open	14"
Body Length	4-1/2"
Turnbuckle Size	5/16" x 4-1/2"
Finish	Galvanized
Product Weight	.5 lbs.
Standards	Meets or exceeds all requirements of ASTM F-1145.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- NOT FOR OVERHEAD LIFTING. This product is rated for cargo securement only.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/galvanized-turnbuckle-hook-hook-5-16-x-4-1-2