

TURNBUCKLES > GALVANIZED JAW & JAW

1-1/2" x 24" Jaw & Jaw Galvanized Turnbuckle

SKU: JJTBGV112X24 Item weight: 40 lbs

WORKING LOAD LIMIT	LENGTH
21,400 lbs.	43.50"

SPECIFICATIONS

SKU	JJTBGV112X24
Working Load Limit (lbs.)	21,400 lbs.
Safety Factor	5:1
Rated for Overhead Lifting	Yes
Diameter	1-1/2"
Length Closed	43.50"
Length Open	67.53"
Body Length	24"
Jaw Opening	2.09"
Turnbuckle Size	1-1/2" x 24"
Pin Size	1.38"
Finish	Galvanized
Product Weight	40 lbs.
Standards	Meets or exceeds all requirements of ASTM F-1145.
Additional Info	Jaw end fitted with nut, bolt, and cotter

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/galvanized-turnbuckle-jaw-jaw-1-1-2-x24