TURNBUCKLES > GALVANIZED JAW & JAW

1/2" x 12" Jaw & Jaw Galvanized Turnbuckle

SKU: JJTBGV12X12 Item weight: 2.2 lbs

WORKING LOAD LIMIT
2,200 lbs.

LENGTH
19"

SPECIFICATIONS

SKU	JJTBGV12X12
Working Load Limit (lbs.)	2,200 lbs.
Safety Factor	5:1
Rated for Overhead Lifting	Yes
Diameter	1/2"
Length Closed	19"
Length Open	32.25"
Body Length	12"
Jaw Opening	0.63
Turnbuckle Size	1/2" x 12"
Pin Size	0.41
Finish	Galvanized
Product Weight	2.4 lbs.
Standards	Meets or exceeds all requirements of ASTM F-1145.
Additional Info	Jaw end fitted with nut and bolt assembly

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 12, 2026.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/galvanized-turnbuckle-jaw-jaw-1-2-x-12

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 12, 2026.