



LIFTING BEAMS AND SPREADER BARS > LOW HEADROOM ADJUSTABLE

Low Headroom Adjustable Lifting Beam | 40,000 lb. Capacity | 25' to 30' Spread

SKU: LBLHA40K30 Item weight: 3,880 lbs

WORKING LOAD LIMIT	LENGTH	MATERIAL
40,000 lbs.	367"	Steel

SPECIFICATIONS

SKU	LBLHA40K30
Working Load Limit (lbs.)	40,000 lbs.
Safety Factor	3:1
Rated for Overhead Lifting	Yes
Overall Length	367"
Spread	25' - 30'
Bail Dimensions	Inside Width: 5" Inside Length: 9" Top Thickness: 2.5" Thickness: 1.5"
Material	Steel
Finish	High visibility yellow powder coated paint
Product Weight	3,880 lbs.
Standards	Exceeds all ASME B30.20 and OSHA regulations. Proof loaded per OSHA requirements.
Manufacturer Name	M&W
Brand Part Number	24519
Additional Info	WLL (tons): 20 Headroom: 35.1" Spread Adjustment Increments: 6" per side



SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Lifting and rigging must follow the applicable ASME B30 standards, OSHA regulations and a qualified person's lift plan.

Current price & availability: heavyhaulrigging.com/p/low-headroom-adjustable-lifting-beam-40-000-lb-capacity-25-to-30-s...