WIRE ROPE > 1X7 EHS GUY STRAND WIRE ROPE

7/16" 1x7 EHS Galvanized Guy Wire | 5,000 ft.

SKU: LC17EHSGS716-5000FT Item weight: 2,000 lbs

BREAK STRENGTH	GRADE	LENGTH
10.4 tons / 20,800 lbs.	EHS	5,000'

SPECIFICATIONS

SKU	LC17EHSGS716-5000FT
Assembly Break Strength	10.4 tons / 20,800 lbs.
Grade	EHS
Wire Rope Diameter	7/16"
Length	5,000'
Wire Rope Class	1x7
Core	IWRC
Finish	Galvanized
Product Weight	2,000 lbs.
Weight Per Foot	0.4 lbs.
Standards	Meets all requirements of ASTM A475-03

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/7-16-1x7-ehs-galvanized-guy-wire-5-000-ft

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.