WIRE ROPE > 6X19 GALVANIZED WIRE ROPE

1-1/8" 6x19 Galvanized Wire Rope - EIPS IWRC | 250' Coil

SKU: LF118EIG69-250FT Item weight: 585 lbs

BREAK STRENGTH	GRADE	LENGTH
65 tons / 130,000 lbs.	EIPS	250'

SPECIFICATIONS

SKU	LF118EIG69-250FT
Assembly Break Strength	65 tons / 130,000 lbs.
Rated for Overhead Lifting	Yes
Grade	EIPS
Wire Rope Diameter	1-1/8"
Length	250'
Wire Rope Class	6x19
Core	IWRC
Finish	Galvanized
Product Weight	585 lbs.
Weight Per Foot	2.34 lbs.
Standards	Meets all dimensional and strength requirements of Federal Specification RR-W-410 (latest revision) and ASTM A1023
Additional Info	Right Hand Regular Lay

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.

Current price & availability: heavyhaulrigging.com/p/1-1-8-6x19-galvanized-wire-rope-eips-iwrc-250-coil

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.