WIRE ROPE > 6X37 BRIGHT STEEL CORE WIRE ROPE

# 1/2" 6x37 Bright Wire Rope - EIPS IWRC | 250' Coil

SKU: LF12EIB637-250FT Item weight: 115 lbs

| BREAK STRENGTH | GRADE | LENGTH |
|---|---|---|
| 13.3 tons / 26,600 lbs. | EIPS | 250' |

## SPECIFICATIONS

| | |
|---|---|
| **SKU** | LF12EIB637-250FT |
| **Assembly Break Strength** | 13.3 tons / 26,600 lbs. |
| **Rated for Overhead Lifting** | Yes |
| **Grade** | EIPS |
| **Wire Rope Diameter** | 1/2" |
| **Length** | 250' |
| **Wire Rope Class** | 6x37 |
| **Rope Construction** | 6x36 |
| **Core** | IWRC |
| **Finish** | Bright |
| **Product Weight** | 115 lbs. |
| **Weight Per Foot** | 0.46 lbs. |
| **Standards** | Meets all dimensional and strength requirements of Federal Specification RR-W-410 (latest revision) and ASTM A1023 |
| **Additional Info** | Right Hand Regular Lay |


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.

### SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

**Current price & availability: heavyhaulrigging.com/p/1-2-6x37-bright-wire-rope-eips-iwrc-250-coil**



Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.