WIRE ROPE > 6X19 GALVANIZED WIRE ROPE

1/2" 6x19 Galvanized Wire Rope - EIPS IWRC | 500' Coil

SKU: LF12EIG619-500FT Item weight: 230 lbs

BREAK STRENGTH	GRADE	LENGTH
13.3 tons / 26,600 lbs.	EIPS	500'

SPECIFICATIONS

SKU	LF12EIG619-500FT
Assembly Break Strength	13.3 tons / 26,600 lbs.
Rated for Overhead Lifting	Yes
Grade	EIPS
Wire Rope Diameter	1/2"
Length	500'
Wire Rope Class	6x19
Core	IWRC
Finish	Galvanized
Product Weight	230 lbs.
Weight Per Foot	0.46 lbs.
Standards	Meets all dimensional and strength requirements of Federal Specification RR-W-410 (latest revision) and ASTM A1023
Additional Info	Right Hand Regular Lay

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 15, 2026.

Current price & availability: heavyhaulrigging.com/p/1-2-6x19-galvanized-wire-rope-eips-iwrc-500-coil

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 15, 2026.