WIRE ROPE > 1X7 EHS GUY STRAND WIRE ROPE

3/16" 1x7 EHS Galvanized Guy Wire | 2500 Ft.

SKU: LF17EHSGS316-2500FT Item weight: 182.5 lbs

BREAK STRENGTH	GRADE	LENGTH
1.995 tons / 3,990 lbs	EHS	2,500'

SPECIFICATIONS

SKU	LF17EHSGS316-2500FT
Assembly Break Strength	1.995 tons / 3,990 lbs
Grade	EHS
Wire Rope Diameter	3/16"
Length	2,500'
Wire Rope Class	1x7
Core	IWRC
Finish	Galvanized
Product Weight	182.5 lbs.
Weight Per Foot	.073 lbs.
Standards	Meets all requirements of ASTM A475-06

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/3-16-1x7-galvanized-guy-wire-2500-ft

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 16, 2026.