WIRE ROPE > 1X7 EHS GUY STRAND WIRE ROPE

5/16" 1x7 EHS Galvanized Guy Wire | 500 ft.

SKU: LF17EHSGS516-500FT Item weight: 105 lbs

BREAK STRENGTH	GRADE	LENGTH
5.6 tons / 11,200 lbs.	EHS	500'

SPECIFICATIONS

SKU	LF17EHSGS516-500FT
Assembly Break Strength	5.6 tons / 11,200 lbs.
Grade	EHS
Wire Rope Diameter	5/16"
Length	500'
Wire Rope Class	1x7
Core	IWRC
Finish	Galvanized
Product Weight	105 lbs.
Weight Per Foot	0.225 lbs.
Standards	Meets all requirements of ASTM A475-03

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/5-16-1x7-ehs-galvanized-guy-wire-500-ft

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.