WIRE ROPE > 6X26 IMPACT SWAGED WIRE ROPE

1" 6x26 Impact Swaged Bright Wire Rope - EIPS IWRC | 250 ft.

SKU: LF1IS626RR-250FT Item weight: 500 lbs

BREAK STRENGTH	GRADE	LENGTH
55 tons / 110,000 lbs.	EIPS	250'

SPECIFICATIONS

SKU	LF1IS626RR-250FT
Assembly Break Strength	55 tons / 110,000 lbs.
Rated for Overhead Lifting	Yes
Grade	EIPS
Wire Rope Diameter	1"
Length	250'
Wire Rope Class	6x26
Core	IWRC
Finish	Bright
Product Weight	500 lbs.
Weight Per Foot	1.54 lbs.
Standards	Meets all dimensional and strength requirements of Federal Specification RR-W-410 (latest revision) and ASTM A1023
Additional Info	Right Hand Regular Lay

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 13, 2026.

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/1-6x26-impact-swaged-bright-wire-rope-eips-iwrc-250-ft

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 13, 2026.