

WIRE ROPE > 19X19 COMPACTED BRIGHT WIRE ROPE

3/4" 19x19 Compacted Rotation-Resistant Wire Rope - EIPS IWRC | 500' Coil

SKU: LF34CBW1919-500FT Item weight: 625 lbs

BREAK STRENGTH	GRADE	LENGTH
33.15 tons / 66,300 lbs.	EIPS	500'

SPECIFICATIONS

SKU	LF34CBW1919-500FT
Assembly Break Strength	33.15 tons / 66,300 lbs.
Rated for Overhead Lifting	Yes
Grade	EIPS
Wire Rope Diameter	3/4"
Length	500'
Wire Rope Class	19x19
Core	IWRC
Finish	Bright
Product Weight	625 lbs.
Weight Per Foot	1.25
Standards	Meets all dimensional and strength requirements of Federal Specification RR-W-410 (latest revision) and ASTM A1023
Additional Info	Category 2 Rotation-Resistant Rope Right Hand Regular Lay

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/3-4-19x19-compacted-rotation-resistant-wire-rope-eips-iwrc-500-ft