

WIRE ROPE > 19X19 COMPACTED BRIGHT WIRE ROPE

5/8" 19x19 Compacted Rotation-Resistant Wire Rope - EIPS IWRC | Linear Foot

SKU: LF58CBW1919 Item weight: 0.85 lbs

BREAK STRENGTH	GRADE	LENGTH
22.7 tons / 45,400 lbs.	EIPS	1'

SPECIFICATIONS

SKU	LF58CBW1919
Assembly Break Strength	22.7 tons / 45,400 lbs.
Rated for Overhead Lifting	Yes
Grade	EIPS
Wire Rope Diameter	5/8"
Length	1'
Wire Rope Class	19x19
Core	IWRC
Finish	Bright
Product Weight	0.85 lbs.
Weight Per Foot	0.85
Standards	Meets all dimensional and strength requirements of Federal Specification RR-W-410 (latest revision) and ASTM A1023
Additional Info	Category 2 Rotation-Resistant Rope Right Hand Regular Lay

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Current price & availability: heavyhaulrigging.com/p/rotation-resistant-compacted-bright-wire-rope-eips-iwrc-19-x-19-clas...