WIRE ROPE > 6X19 GALVANIZED WIRE ROPE

5/8" 6x19 Galvanized Wire Rope - EIPS IWRC | Linear Foot

SKU: LF58EIG619 Item weight: 0.72 lbs

BREAK STRENGTH	GRADE	LENGTH
20.6 tons / 41,200 lbs.	EIPS	1'

SPECIFICATIONS

SKU	LF58EIG619
Assembly Break Strength	20.6 tons / 41,200 lbs.
Rated for Overhead Lifting	Yes
Grade	EIPS
Wire Rope Diameter	5/8"
Length	1'
Wire Rope Class	6x19
Core	IWRC
Finish	Galvanized
Product Weight	0.72 lbs.
Weight Per Foot	0.72
Standards	Meets all dimensional and strength requirements of Federal Specification RR-W-410 (latest revision) and ASTM A1023
Additional Info	Right Hand Regular Lay

SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 1, 2026.

Current price & availability: heavyhaulrigging.com/p/galvanized-wire-rope-eips-iwrc-6x19-class-5-8-lineal-foot

Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 1, 2026.