WIRE ROPE > 19X19 COMPACTED BRIGHT WIRE ROPE

# 9/16" 19x19 Compacted Rotation-Resistant Wire Rope - EIPS IWRC | 500 Feet

SKU: LF916CBW1919-500FT Item weight: 345 lbs

| BREAK STRENGTH | GRADE | LENGTH |
|---|---|---|
| 18.75 tons / 37,500 lbs. | EIPS | 500' |

## SPECIFICATIONS

| | |
|---|---|
| **SKU** | LF916CBW1919-500FT |
| **Assembly Break Strength** | 18.75 tons / 37,500 lbs. |
| **Grade** | EIPS |
| **Wire Rope Diameter** | 9/16" |
| **Length** | 500' |
| **Wire Rope Class** | 19x19 |
| **Core** | IWRC |
| **Finish** | Bright |
| **Product Weight** | 345 lbs. |
| **Weight Per Foot** | 0.69 |
| **Standards** | Meets all dimensional and strength requirements of Federal Specification RR-W-410 (latest revision) and ASTM A1023 |
| **Additional Info** | Category 2 Rotation-Resistant Rope Right Hand Regular Lay |

### SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 13, 2026.

**Current price & availability: heavyhaulrigging.com/p/9-16-19x19-compacted-rotation-resistant-wire-rope-eips-iwrc-500-feet**


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 13, 2026.