LOAD CELLS > TENSION LOAD CELLS

# Straightpoint® 200 T Loadlink Plus - LLP200T

SKU: LLP-200-T Item weight: 180.8 lbs

CAPACITY

**440,000 lbs.**

## SPECIFICATIONS

| | |
|---|---|
| **SKU** | LLP-200-T |
| **Safety Factor** | 5:1 |
| **Load Capacity** | 440,000 lbs. |
| **Pin Size** | 4-3/4" |
| **Type** | Standard Load Cell |
| **Power Source** | 9v PP3 battery |
| **Accuracy** | +/- 0.1% of Full Scale |
| **Resolution** | 200 lbs. |
| **Operating Temperature** | -10° to +50°C \| 14° to 122° F |
| **Battery Life** | 80 hours continuous |
| **Display Type** | 6 digit 1" LCD |
| **Product Weight** | 180.8 lbs. |
| **Standards** | IP65 |
| **Manufacturer Name** | Crosby Straightpoint |
| **Brand Part Number** | LLP200T / 2789043 |


Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.

## SAFETY INFORMATION

- Never exceed the Working Load Limit (WLL). The WLL is the maximum load the product is rated to handle in service.
- Inspect before every use. Remove from service if cut, worn, abraded, stretched, cracked, bent, corroded, heat-damaged or missing its identification tag or marking.
- Protect webbing, rope and chain from sharp edges and corners with edge protection.
- Cargo securement on commercial vehicles must meet FMCSA 49 CFR Part 393, Subpart I (aggregate WLL and minimum tie-down rules).

**Current price & availability: heavyhaulrigging.com/p/straightpoint-200-t-loadlink-plus-llp200t**



Specifications are for reference and may change without notice. Always follow the ratings marked on the product itself. Generated Nov 3, 2026.